

SUPER GRIP CUT LEVEL D NITRILE GLOVE



- HPPE & FIBRE LINER
- 13G GAUGE
- SANDY NITRILE
- PALM DIP
- SPANDEX CUFF
- CUT LEVEL D



MECHANICAL RISK PROFILE

The gloves performance against mechanical risk tests as stipulated by the EN388 standard.

ABRASION	1	2	3	4		
CUT (COUP)	X	X	X	X	X	
TEAR	1	2	3	4		
PENETRATION	1	2	3	4		
CUT (TDM-100)	A	B	C	D	E	F

SANDY NITRILE COATING PROPERTIES

Sandy nitrile is a synthetic rubber-like compound with sand particles. It has great flexibility and excellent abrasion resistance. Nitrile is resistant to the permeation of liquids and oils and offers superior grip in wet, dry & oily conditions.

DRY GRIP	1	2	3	4	5
WET GRIP	1	2	3	4	5
OIL GRIP	1	2	3	4	5
DEXTERITY	1	2	3	4	5
DURABILITY	1	2	3	4	5
DIVERSITY	1	2	3	4	5

SPECIFICATIONS:

- 🕒 Seamless 13g grey woven HPPE & fibre liner provides increased comfort, dexterity, breathability and protection assurance.
- 🕒 Sandy nitrile palm coating provides a superior grip in wet, dry & oily conditions with a softer feel, excellent abrasion, cut, tear and penetration resistance.
- 🕒 Excellent resistance to liquid & oil permeation.
- 🕒 Knit wrist helps prevent dust & debris from entering the glove liner.
- 🕒 Breathable back for comfort.
- 🕒 Sizes: 7/S, 8/M, 9/L, 10/XL, 11/XXL

APPLICATIONS:

- 🕒 Mechanical / Automotive
- 🕒 Sanitation / Waste / Recycling
- 🕒 Glass / Steel
- 🕒 Paper Handling
- 🕒 Sharp Object Handling
- 🕒 Wood Working
- 🕒 Construction

