

HANVO GENERAL HANDLING LATEX GLOVE



EN388:2016



MECHANICAL RISK PROFILE

Performance against mechanical risk tests as stipulated by the EN388 standard.

ABRASION	1	2	3	4	5
CUT	1	2	3	4	5
TEAR	1	2	3	4	5
PENETRATION	1	2	3	4	5

LATEX COATING PROPERTIES

Latex is made from natural rubber latex. It has good flexibility, durability and a superior wet & dry grip.

DRY GRIP	1	2	3	4	5
WET GRIP	1	2	3	4	5
OIL GRIP	1	2	3	4	5
DEXTERITY	1	2	3	4	5
DURABILITY	1	2	3	4	5
DIVERSITY	1	2	3	4	5

SPECIFICATIONS

- Seamless 13 gauge blue woven polyester liner offers comfort, dexterity and breathability.
- Latex crinkle palm coating provides excellent grip in wet & dry conditions with good abrasion and tear resistance.
- Knit wrist helps prevent dust & debris from entering the glove liner.
- Washable to extend the glove life and reduce replacement costs.
- Breathable back for comfort.
- Sizes: 8/M, 9/L, 10/XL, 11/XXL.
- Dimensions (+/-5%): 255mm x 102mm x 55g.
- Packaging: Individually packaged pairs, 12 pairs per bag, 120 pairs per carton.

FEATURES

- Strong Grip
- Flexible
- Light
- Breathable
- Ergonomically Shaped
- Soft Feel

APPLICATIONS

- Automotive
- General Duty
- Gardening / Agriculture
- Assembly / Manufacturing
- Transport / Warehousing