

HANVO FULL DIP OIL/WET HANDLING NITRILE GLOVE



EN388:2016



MECHANICAL RISK PROFILE

Performance against mechanical risk tests as stipulated by the EN388 standard.

ABRASION	1	2	3	4	5
CUT	1	2	3	4	5
TEAR	1	2	3	4	5
PENETRATION	1	2	3	4	5

NITRILE COATING PROPERTIES

Sandy nitrile is a synthetic rubber-like compound with sand particles. It has great flexibility and excellent abrasion resistance.

DRY GRIP	1	2	3	4	5
WET GRIP	1	2	3	4	5
OIL GRIP	1	2	3	4	5
DEXTERITY	1	2	3	4	5
DURABILITY	1	2	3	4	5
DIVERSITY	1	2	3	4	5

SPECIFICATIONS

- Seamless 15 gauge black woven polyester liner provides increased comfort, dexterity.
- Sandy nitrile palm coating provides a superior grip in wet, dry & oily conditions. Excellent abrasion, cut, tear & penetration resistance.
- Full nitrile dip provides complete resistance to liquid & oil permeation.
- Knit wrist helps prevent dust & debris from entering the glove liner.
- Washable to extend the glove life and reduce replacement costs.
- Sizes: 8/M, 9/L, 10/XL, 11/XXL.
- Dimensions (+/-5%): 255mm x 102mm x 76g.
- Packaging: Individually packaged pairs, 12 pairs per bag, 120 pairs per carton.

FEATURES

- Strong Grip
- Ergonomically Shaped
- Abrasion Resistance
- Flexible
- Light
- Liquid & Oil Resistance

APPLICATIONS

- Automotive
- Construction
- Cold Handling
- Assembly / Manufacturing
- Water / Sanitation
- Gardening / Agriculture
- Machinery / Equipment
- Waste / Recycling