

## HANVO CUT RESISTANT LEVEL 5/D NITRILE GLOVE



EN388:2016



### MECHANICAL RISK PROFILE

Performance against mechanical risk tests as stipulated by the EN388 standard.

ABRASION	1	2	3	4		
CUT(COUP)	X	X	X	X	X	
TEAR	1	2	3	4		
PENETRATION	1		3	4		
CUT(TDM-100)	A	B	C	D	E	F

### NITRILE COATING PROPERTIES

Sandy nitrile is a synthetic rubber-like compound with sand particles. It has great flexibility and excellent abrasion resistance.

DRY GRIP	1	2	3	4	5
WET GRIP	1	2	3	4	5
OIL GRIP	1	2	3	4	5
DEXTERITY	1	2	3	4	5
DURABILITY	1	2	3	4	5
DIVERSITY	1	2	3	4	5

### SPECIFICATIONS

- Seamless 13 gauge grey woven HPPE & fibre liner provides comfort, flexibility and cut resistant level 5/D protection.
- Sandy nitrile palm coating provides a superior grip in wet, dry & oily conditions. Excellent abrasion, cut, tear & penetration resistance.
- Excellent resistance to liquid & oil permeation.
- Knit wrist helps prevent dust & debris from entering the glove liner.
- Washable to extend the glove life and reduce replacement costs.
- Sizes: 8/M, 9/L, 10/XL, 11/XXL.
- Dimensions (+/-5%): 255mm x 102mm x 110g.
- Packaging: Individually packaged pairs, 12 pairs per bag, 120 pairs per carton.

### FEATURES

- Strong Grip
- Light
- Liquid & Oil Resistance
- Flexible
- Cut Resistant
- Ergonomically Shaped
- Abrasion Resistance

### APPLICATIONS

- Automotive
- Transport / Warehousing
- Steel / Sharp Object
- Assembly / Manufacturing
- Construction
- Gardening / Agriculture
- Machinery / Equipment
- Waste / Recycling